



# TECHNOFACADE 35

## STONE WOOL

### PRODUCT DESCRIPTION

TECHNOFACADE 35 are non-combustible, hydrophobic thermal and sound insulation boards with a disturbed fiber arrangement, made of stone wool.

### APPLICATION

As a layer for thermal, acoustic and fire insulation in industrial and civil construction. Intended for use inside and outside buildings in jointless thermal insulation systems (ETICS).



THICKNESS RANGE 50 - 300 [mm]

### DECLARED PARAMETERS

Parameter	Symbol	Unit	Value	Method
Declared thermal conductivity	$\lambda_D$	W/mK	0,035	EN 12667, EN 12939
Thickness tolerance class	T	-	T5	EN 823
Dimensional stability under certain temperature and humidity conditions	DS(70,90)	%	$\leq 1$	EN 1604
Compressive stress at 10% deformation	CS(10)	kPa	$\geq 30$	EN 826
Tensile strength perpendicular to the faces	TR	kPa	$\geq 10$	EN 1607
Point load at 5 mm deformation	PL(5)	N	$\geq 200$	EN 12430
Air flow resistivity	AFr	kPa·s/m <sup>2</sup>	NPD	EN 9053-1
Short-term water absorption	WS	kg/m <sup>2</sup>	$\leq 1$	EN 29767
Long-term water absorption	WL(P)	kg/m <sup>2</sup>	$\leq 3$	EN 16535
Water vapor diffusion resistance coefficient	MU	-	MU1	EN 13162+A1
Reaction to fire	RtF	-	A1	EN 13501-1, EN 15715 NPD - No Performance Declared

### DECLARED THERMAL REISTANCE

Value of declared thermal resistance $R_D$															
Thickness [mm]	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150
$R_D$ [m <sup>2</sup> K/W]	-	-	-	-	1,35	1,65	1,95	2,20	2,50	2,80	3,05	3,35	3,65	3,95	4,20
Thickness [mm]	160	170	180	190	200	210	220	230	240	250	260	270	280	290	300
$R_D$ [m <sup>2</sup> K/W]	4,50	4,80	5,05	5,35	5,65	5,95	6,20	6,50	6,80	7,05	7,35	7,65	7,95	8,20	8,50



**LOGISTICS INFORMATION**

Full truck loading: 22 standard pallets / 11 pallets marked with H2,6

**STORAGE**

The product may only be stored outdoors in an intact, originally packed pallet. Protected against the harmful effects of weather conditions and set on a dry and stable surface.

Maximum stacking height of pallets up to three meters.

**ADDITIONAL INDICATIONS ON THE LABEL**

**H2,6** - pallet with a height of about 2,6 m / twice the amount of the product compared to a standard pallet

**(PILLAR)** - product on a stone wool base instead of a wooden pallet

**(X slabs)** - number of slabs in the pack

**(N) / (S)** - code of the region



Certificate number: **1454-CPR-0292**

Designation code: **MW-EN 13162-T5-DS(70,90)-CS(10)30-TR10-PL(5)200-WS-WL(P)-MU1**

Declaration of performance no: **TNI/ETICS/TF35/2022\_11**

